

LED UNDER WATER LIGHT WATER PROOF

24 months warranty against any manufacturing defect.

Item Code	Power (Rated)	Voltage	LED Brand	Protection	Dimensions (mm)
DLIG1-42-12-CRS/30	01w	12V/24V	CREE (USA)	IP68	L:42 x W:42 x H:80
DLIG3-52-12-CRS/30	03w	12V/24V	CREE (USA)	IP68	L:52 x W:52 x H:80
DLIG3-100-24-CRS/30	03w	12V/24V	BRIDGELUX (USA)	IP68	L:100 x W:100 x H:75
DLIG6-125-24-CRS/30	06w	12V/24V	BRIDGELUX (USA)	IP68	L:125 x W:125 x H:85
DLUW6-120-SRSN/27	06w	12V	EPISTAR (Taiwan)	IP68	L:120 x W:120 x H:150
DLUW6-125-SRSN/27	06w	12V	EPISTAR (Taiwan)	IP68	L:125 x W:125 x H:180
DLUW6-120-SRS/RGB	06w	12V	BRIDGELUX (USA)	IP68	L:120 x W:120 x H:155
DLUW9-145-SRS/RGB	09w	12V	BRIDGELUX (USA)	IP68	L:145 x W:145 x H:170
DLUW18-290-SRC/30	18w	12V/24V	EPISTAR (Taiwan)	IP68	L:277 x W:277 x H:60
DLUW36-290-SRC/30	36w	12V/24V	EPISTAR (Taiwan)	IP68	L:277 x W:277 x H:60

TRANSFORMER options

DLT5-12-68/B	05VA 12V IP68 L:46 x W:39 x H:36	DLT20-24-68/B	20VA 24V IP68 L:110 x W:70 x H:74
DLT10-12-68/B	10VA 12V IP68 L:81 x W:51 x H:63	DLT40-24-68/B	40VA 24V IP68 L:110 x W:70 x H:74
DLT30-12-68/B	30VA 12V IP68 L:110 x W:72 x H:74	DLT105-12-44/B	100w 12V IP44 L:160 x W:130 x H:80
DLT40-12-68/B	40VA 12V IP68 L:110 x W:72 x H:74	DLT200-12-44/B	200w 12V IP44 L:160 x W:130 x H:80
DLT10-24-68/B	10VA 24V IP68 L:81 x W:51 x H:63	DLT600-12-44/B	600w 12V IP44 L:180 x W:150 x H:90



18w/36w



::: Inground Light

::: Inground Light

::: Under Water Light

::: Under Water Light

1w



3w



6w



6w

3w



6w



9w



6w

APPLICATIONS :: Swimming Pool, Fountain, any other artificial under water location