

LED BOUNDARY LIGHT ::: UPDOWN LIGHT OUTDOOR

24 months warranty against any manufacturing defect.

Item Code (WARM)	Power (Rated)	LED Brand	Appearance	Protection	Dimensions (mm)
DLSR12-260-SRB/30	12w	EPISTAR (Taiwan)	RECTNAG. (Black)	IP65	L:260 x W:125 x H:125
DLSR8-108-SSB/30	08w	EPISTAR (Taiwan)	SQUARE (Black)	IP65	L:108 x W:108 x H:80
DLSR8-108-SSG/30	08w	EPISTAR (Taiwan)	SQUARE (Grey)	IP65	L:108 x W:108 x H:80
DLSR10-200-SRG/30	10w	BRIDGELUX (USA)	ROUND (Black)	IP65	L:200 x W:130 x H:70
DLUD8-95-SRB/30	08w	EPISTAR (Taiwan)	ROUND (Black)	IP65	L:105 x W:95 x H:87
DLUD10-130-SRG/30	1x10w	BRIDGELUX (USA)	CYLINDER (Grey)	IP65	L:130 x W:90 x H:130
DLUD20-170-SRG/30	2x10w	BRIDGELUX (USA)	CYLINDER (Grey)	IP65	L:170 x W:90 x H:130
DLUD4-130-SRB/30	4x01w	CREE (USA)	ROUND (Black)	IP65	L:130 x W:130 x H:55
DLUD10-200-SRG/30	2x05w	BRIDGELUX (USA)	HYPERBOLOID (Grey)	IP65	L:200 x W:100 x H:85
DLUD10-1695-2G/30	2x05w	BRIDGELUX (USA)	RECTNAG. (Grey)	IP65	L:165 x W:95 x H:55
DLUD2-80-SOG/30	2x01w	CREE (USA)	OVAL (Black)	IP65	L:80 x W:80 x H:34
DLUD6-170-SOG/30	6x01w	CREE (USA)	OVAL (Grey)	IP65	L:170 x W:70 x H:40
DLSC6-100-SSG/30	2x03w	BRIDGELUX (USA)	RECTNAG. (Black)	IP66	L:100 x W:100 x H:50
DLUD3-87-SSG/30	1x03w	CREE (USA)	RECTNAG. (Black)	IP65	L:82 x W:78 x H:65
DLUD6-162-SRG/30	2x03w	CREE (USA)	RECTNAG. (Black)	IP65	L:162 x W:80 x H:65
DLUD3-95-SRG/30	2+1w	CREE (USA)	RECTNAG. (Black)	IP65	L:85 x W:47 x H:54



:: Security Light

2w



8w



1x10w



1x8w



1x10w



2x10w



4x1w



2x5w



2x5w



2x3w




6x1w




2x5w



1x3w



2x3w



2+1w

Voltage ::: 85V-265V

CCT (K) :::

3000K

APPLICATIONS ::: Boundry wall, Building Façade or any outdoor location need to be illuminated.