

### LED INGROUND LIGHT OUTDOOR WATER PROOF

24 months warranty against any manufacturing defect.

Item Code (WARM)	Power (Rated)	Voltage	Beam	Protection	Dimensions (mm)
DLIG1-42-22-CRA/30	01w	85V-265V	30°	IP67	L:42 x W:42 x H:80
DLIG1-42-12-CRS/30	01w	12V	30°	IP68	L:42 x W:42 x H:80
DLIG1-52-22-CRS/30	01w	85V-265V	30°	IP68	L:52 x W:52 x H:80
DLIG3-52-22-CRA/30	03w	85V-265V	30°	IP67	L:52 x W:52 x H:80
DLIG3-52-12-CRS/30	03w	12V	30°	IP68	L:52 x W:52 x H:80
DLIG3-75-22-CRS/30	03w	85V-265V	30°	IP68	L:75 x W:75 x H:98
DLIG3-100-22-CRS/30	03w	85V-265V	30°	IP68	L:100 x W:100 x H:75
DLIG6-125-CRSN/27	06w	85V-265V	30°	IP68	L:125 x W:125 x H:90
DLIG7-100-22-CRS/30	07w	85V-265V	60°	IP67	L:100 x W:100 x H:80
DLIG15-150-22-CRS/30	15w	85V-265V	60°	IP67	L:150 x W:150 x H:92
DLIG3-152-22-CRS/30	03w	85V-265V	1D x 30°	IP68	L:52 x W:52 x H:80
DLIG3-252-22-CRS/30	03w	85V-265V	2D x 30°	IP68	L:52 x W:52 x H:80

#### TRANSFORMER options

DLT5-12-68/B	05VA 12V IP68 L:46 x W:39 x H:36	DLT30-12-68/B	30VA 12V IP68 L:110 x W:72 x H:74
DLT10-12-68/B	10VA 12V IP68 L:81 x W:51 x H:63	DLT40-24-68/B	40VA 12V IP68 L:110 x W:72 x H:74



::: Inground Light

::: Inground Light



::: Inground Light

::: Inground Light -Directional



Beam Angle :: 30°-60°

Appearance :: SS



APPLICATIONS :: Swimming Pool, Fountain, any other artificial under water location